

HHD 5507

SOLVENT FREE POLYURETHANE ADHESIVE



PRODUCT DESCRIPTION

HHD 5507 is a one-component, solvent-free, moisture curing polyurethane adhesive. Once it has been dispensed, the adhesive will react with ambient moisture or water content of the substrates, to yield a cross-linked thermoset adhesive. HHD 5507 contains a fluorescent agent allowing for UV inspection.

KEY FEATURES

- → Excellent adhesion to a variety of substrates including plastic and metal
- → Good air tightness
- → Anti-Creep at high temperature
- → Good aging resistance
- → Precision dispensing and good stability

METHOD OF USE

HHD 5507 can be applied through a usual syringe type melting equipment. The weight of coating can vary according to the substrates and applications.

APPLICATIONS

HHD 5507 has been specifically designed for acoustic assembly.

STORAGE

HHD 5507 should be stored in a dry place at a temperature ranging between 15°C and 25°C. It should be processed immediately after the container has been opened.

HEALTH/SAFETY

Read Material Safety Data Sheet before using and handling this product. MSDS is available upon request.

Bostik an Arkema company www.bostik.com born2bond.bostik.com

TECHNICAL DATA

	• • • • • • • • • • • • • • • • • • •	
CHARACTERISTIC	VALUE	
Appearance (solid)	White to Yellowish	
Brookfield Viscosity thermosel @ 110°C	1,700~2,700[mPa.s](27#)	
Open time*	5~7[min]	
Density	1.0~1.1[g/cm³]	
Tensile Strength**	>10[MPa]	
Elongation at break**	>800[%]	
Application Temperature	100~120[°C]	

*Open time is an application factor that depends on the environment temperature, substrates and application process.

**Cured for 8 days, curing conditions are 20°C-25°C, R.H.60%-70%

CURING TIME

The cure rate depends on the substrate type, moisture permeability and ambient conditions. HHD 5507 exhibits high strength instantly after being joined. However, optimum properties can be attained after one to five days at room temperature.

PACKAGING

30mL – White PP plastic syringes

CLEANING

Remove uncured waxy material by scraping with a putty knife or similar tool. For cured material, remove by cutting or sanding. Do not use any heat or flame fire to remove adhesive.

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not guarantee the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

PRODUCT DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BOSTIK'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bostik does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS. Nothing contained herein constitutes a license to practice under any patent, and it should not be construed as an inducement to infringe any patent. You are advised to take appropriate steps to be sure that any proposed use of the products will not result in patent infringement.

The information provided herein relates only to the specific products designated and may not be applicable when such products are used in combination with other materials or in any process. The product is sold pursuant to a supply agreement and/or Bostik's Terms and Conditions of Sale. which set forth the sole warranty, if any, that applies to the product. NO OTHER WARRANTY, EXPRESS OR IMPLIED. INCLUDING WITHOUT LIMITATION ANY WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR WARRANTY OF MERCHANTABILITY, IS MADE CONCERNING THE PRODUCTS DESCRIBED OR THE INFORMATION PROVIDED HEREIN, AND TO THE MAXIMUM EXTENT ALLOWED BY LAW, SUCH WARRANTIES ARE HEREBY DISCLAIMED. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW.

HHD 5507

