



MULTIPLE STRENGTHS



UP TO 180°C



MULTIPLE VISCOSITIES

PIPE SEALING

Born2Bond™ Pipe Sealing anaerobic adhesives are a reliable, adaptable solution, suitable for all types of threaded metal pipes and fittings, and both new installations and preventative maintenance. Filling and sealing all voids, these single component adhesives provide 100% surface-to-surface contact, achieving a cohesive, durable connection that will not fail even when subjected to vibration, extreme temperatures or chemical substances. A convenient, cost-effective alternative to conventional sealing alternatives like hemp or PTFE tapes, these adhesives eliminate the need for additional inventory.

FEATURES

- 100% connection – no loosening
- Vibration resistant
- Corrosion prevention
- Single component
- Variety of viscosities and strengths
- Suitable for active and passive metals

TYPICAL APPLICATIONS

- Engines and powertrains
- Pumps and compressors
- Liquid and gas storage
- Hydraulic systems
- Metal pipes and fittings


BENEFITS

- Increased reliability
- Ease of application
- Reduced costs
- Reduced storage requirements



| | PA-67 | PA-77 | PA-42 |
|-------------------------------------------------------------|--------------------------------|--------------------------------|--------------------------------|
| STRENGTH | Medium | Medium | Medium |
| VISCOSITY (mPa.s) | >20,000 | 80,000-90,000 | 400-800 |
| FIXTURE TIME | > 15-20 min | 60 min | 10-20 min |
| BREAKAWAY STRENGTH ON STEEL [ISO 10964] LOOSE | > 4.5 ft-lb | 8 ft-lb | 11 ft-lb |
| COLOR | White | Yellow | Brown |
| TEMPERATURE RANGE | -67 to 400°F (-55 to 204°C) | -67 to 356°F (-55 to 180°C) | -67 to 302°F (-55 to 150°C) |

TDS and SDS available on request



DISCLAIMER

Bostik offers this Product Catalogue for descriptive and informational use only. The Product Catalogue is not a warranty, a contract or a substitute for expert or professional advice.

The statements, technical information and recommendations contained herein are not exhaustive, are believed to be accurate as of the date hereof, and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. The Product Catalogue relies upon your knowledge and input, and as such, its results are based solely upon the information you provide and the choices that you make. Since the conditions and methods of use of the products and the information relied upon by you are beyond our control, Bostik expressly disclaims any and all liability and damages that may arise from any use of the Product Catalogue, the products, the results therefrom, or reliance on the information contained herein.

The Product Catalogue is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use, the recommendations contained in it, any output and your selections. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use. Bostik does not guarantee the reliability, completeness, use, or function of the Product Catalogue or any recommendations arising therefrom. The data and information contained in the Product Catalogue is provided 'AS IS'.

The information provided herein relates only to the specific products designated and may not be applicable when such products are used in combination with other materials or in any process. **Bostik encourages you to always read and understand (1) the Technical Data Sheet ("TDS") and (2) the Safety Data Sheet ("SDS") for all products, which are located on our corporate website or are available upon request.** You are welcome and encouraged to contact your customer service representative to discuss your specific requirements and to determine what product is appropriate for you and your applications.

Nothing contained herein constitutes a license to practice under any patent, and it should not be construed as an inducement to infringe any patent. You are advised to take appropriate steps to be sure that any proposed use of the products will not result in patent infringement.

